





BarraCuda SATA SSD

Upgrade your drive. Accomplish more. Easily upgrade to SSD speeds. Seagate[®] BarraCuda[™] SATA SSD brings fast SSD

Seagate^(®) BarraCuda[™] SATA SSD brings fast SSD speeds to your PC upgrade. Improve performance and faster processing with sequential read/writes of up to 540/510 MB/s. Enjoy an easy plug-and-play upgrade with a slim 2.5x7mm form factor and SATA 6 Gb/s connection. This drive includes Seagate DiscWizard[™] software to migrate data and SeaTools[™] software to monitor performance.

Key Features

Upgrade Your Speed

Leverage a SATA SSD that provides up to 20× faster speeds than hard drives and harness high sequential read/write speeds (up to 540/510 MB/s) for more responsive downloads, installs and multitasking.


Easy plug-and-play

Upgrade from hard drives with universal plug-and-play compatibility to any SATA connection.

BARRACUDA

Low active power requirements

Extend the battery life of your laptop with low active power requirements of up to 1.4W.



BARRACUDA SATA SSD

Durable for the long run

Improve durability over the long haul with up to 1,200 TB TBW (Total Bytes Written), shock and vibration resistance, and rely on a robust 3-year limited warranty and 1.8M hours mean time between failures (MTBF).

Rely on DiscWizard and SeaTools

Migrate and clone data from previous drive using free Seagate DiscWizard[™] software. Monitor drive health, performance, and firmware updates with free Seagate SeaTools[™] software.



RETAIL PACKAGING	BOX DIMENSIONS	MASTER CARTON DIMENSIONS	PALLET DIMENSIONS
Length (in/mm)	0.555 in/14.1 mm	7.717 in/196 mm	48.031 in/1220 mm
Width (in/mm)	5.236 in/133 mm	12.126 in/308 mm	20 in/508 mm
Depth (in/mm)	7.008 in/178 mm	6.339 in/161 mm	37.283 in/947 mm
Weight (lb/kg)	0.159 lb/0.072 kg	3.968 lb/1.8 kg	131.396 lb/59.6 kg
QUANTITIES			
Boxes per Master Carton	20		
Master Cartons per Pallet	30		
Pallet Layers	5		

Seagate[®] BarraCuda[™] SATA SSD

SYSTEM REQUIREMENTS

SATA 6 Gb/s or SATA 3 Gb/s port

```
Windows<sup>®</sup> 11, Windows 10
```

Linux

REGION	MODEL NUMBER	CAPACITY	LIMITED WARRANTY (YEARS)	UPC CODE	EAN CODE	MULTI-PACK UPC
WW	ZA240CV1A002	240GB	3	763649178720	8719706434119	10763649178727
WW	ZA256CV1A002	256GB	3	763649179017	8719706434386	10763649179014
WW	ZA480CV1A002	480GB	3	763649178737	8719706434126	10763649178734
WW	ZA512CV1A002	512GB	3	763649179024	8719706434393	10763649179021
WW	ZA960CV1A002	960GB	3	763649178744	8719706434133	10763649178741
WW	ZA1920CV1A002	1.92TB	3	763649178751	8719706434140	10763649178758
ww	ZA3840CV1A002	3.84TB	3	763649178782	8719706434164	10763649178789

BARRACUDA SATA SSD

SPECIFICATIONS	3.84TB	1.92TB	960GB	512GB	480GB
Standard Model	ZA3840CV10002	ZA1920CV10002	ZA960CV10002	ZA512CV10002	ZA480CV10002
Interface ¹	SATA 6 Gb/s				
Form Factor	2.5 in × 7 mm				
PERFORMANCE					
Sequential Read (Max, MB/s), 128KB ²	540MB/s	540MB/s	540MB/s	540MB/s	540MB/s
Sequential Write (Max, MB/s), 128KB ²	510	510	510	500	500
ENDURANCE/RELIABILITY					
Total Bytes Written (TB)	1,200	600	300	160	170
Mean Time Between Failures (MTBF, hours)	1800000 hr				
Warranty, Limited (years)	3	3	3	3	3
POWER MANAGEMENT					
Active Power, Average (W)	1.40 W	1.35 W	1.30 W	1.25 W	1.25 W
Idle Power, Average (mW)	250	250	250	250	250
ENVIRONMENTAL					
Temperature, Operating Internal (°C)	0 to 70				
Temperature, Nonoperating (°C)	-40°C – 85°C				
Shock, Nonoperating: 0.5ms (Gs)	1500 Gs				
SPECIAL FEATURES					
TRIM	Yes	Yes	Yes	Yes	Yes
S.M.A.R.T.	Yes	Yes	Yes	Yes	Yes
Halogen Free	Yes	Yes	Yes	Yes	Yes
RoHS Compliance	Yes	Yes	Yes	Yes	Yes
PHYSICAL					
Length (mm/in, max)	7.10 mm/0.275 in				
Width (mm/in, max)	70.10 mm/2.759 in				
Height (mm/in, max)	100.40 mm/3.953 in				
Weight (g/lb)	35 g/0.077 lb				

1 Backwards compatible with SATA 3 Gb/s and SATA 1.5 Gb/s 2 Fresh out of box (FOB) performance obtained on newly formatted drive. Performance may vary based on SSD's firmware version, system hardware, and configuration. Performance based on CrystalDiskMark v.6.0 ×64 on Windows 10 host.

SPECIFICATIONS	256GB	240GB	
Standard Model	ZA256CV10002	ZA240CV10002	
nterface ¹			
	SATA 6 Gb/s	SATA 6 Gb/s	
Form Factor	2.5 in × 7 mm	2.5 in × 7 mm	
PERFORMANCE			
Sequential Read (Max, MB/s), 128KB ²	540MB/s	540MB/s	
Sequential Write (Max, MB/s), 128KB ²	490	490	
ENDURANCE/RELIABILITY			
Total Bytes Written (TB)	75	80	
Mean Time Between Failures (MTBF, hours)	1800000 hr	1800000 hr	
Warranty, Limited (years)	3	3	
POWER MANAGEMENT			
Active Power, Average (W)	1.20 W	1.20 W	
Idle Power, Average (mW)	250	250	
ENVIRONMENTAL			
Temperature, Operating Internal (°C)	0 to 70	0 to 70	
Temperature, Nonoperating (°C)	-40°C – 85°C	-40°C – 85°C	
Shock, Nonoperating: 0.5ms (Gs)	1500 Gs	1500 Gs	
SPECIAL FEATURES			
TRIM	Yes	Yes	
S.M.A.R.T.	Yes	Yes	
Halogen Free	Yes	Yes	
RoHS Compliance	Yes	Yes	
PHYSICAL			
Length (mm/in, max)	7.10 mm/0.275 in	7.10 mm/0.275 in	
Nidth (mm/in, max)	70.10 mm/2.759 in	70.10 mm/2.759 in	
leight (mm/in, max)	100.40 mm/3.953 in	100.40 mm/3.953 in	
Veight (g/lb)	35 g/0.077 lb	35 g/0.077 lb	

1 Backwards compatible with SATA 3 Gb/s and SATA 1.5 Gb/s

2 Fresh out of box (FOB) performance obtained on newly formatted drive. Performance may vary based on SSD's firmware version, system hardware, and configuration. Performance based on CrystalDiskMark v.6.0 × 64 on Windows 10 host.

SEAGATE.COM

© 2023 Seagate Technology LLC. All rights reserved. Seagate, Seagate Technology, and the Spiral logo are registered trademarks of Seagate Technology LLC in the United States and/or other countries. BarraCuda, the BarraCuda logo, DiscWizard, and SeaTools are either trademarks or registered trademarks of Seagate Technology LLC or one of its affiliated companies in the United States and/or other countries. All other trademarks or registered trademarks are the property of their respective owners. When referring to drive capacity, one gigabyte, or GB, equals one billion bytes and one terabyte, or TB, equals one trillion bytes. Your computer's operating system may use a different standard of measurement and report a lower capacity. In addition, some of the listed capacity is used for formatting and other functions, and thus will not be available for data storage. Actual data rates may vary depending on operating environment and other factors, such as chosen interface and disk capacity. Seagate reserves the right to change, without notice, product offerings or specifications. DS2128.1-2301US