

CP- UNC-DB21L3C-MDS**2MP Full HD WDR IR Network Dome Camera - 30Mtr.****Main Features**

- 1/2.8" 2MP PS CMOS Image Sensor (0.9071 centimeters)
- 25/30fps@1080P(1920x1080)
- Support Starlight Function
- Instastream and H.264+ Dual-stream encoding
- WDR(120dB), Day/Night (ICR), 3D-DNR, ROI, AWB, AGC, BLC, HLC
- 3.6mm fixed lens (2.8mm optional)
- IR Range of 30 Mtrs, IP67, Micro SD Card, PoE
- Support Built-in Mic
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS Pro



CP- UNC-DB21L3C-MDS

2MP Full HD WDR IR Network Dome Camera - 30Mtr.

Feature

Image Sensor
 Minimum Illumination
 Effective Pixels
 Shutter Speed
 White Balance
 S/N Ratio
 Lens
 Gain Control (AGC)
 Video Compression
 Angle of View
 Back Light Compensation
 Video Streaming
 Resolution
 Motion detection
 Privacy Mask
 ICR
 ROI
 Audio Compression
 Audio
 Bit Rate
 Protocol
 Smart Detection
 Ethernet
 Event Trigger
 User Account
 IR

Specification

1/2.8" 2MP Progressive scan CMOS (0.9071 centimeters)
 0.002 Lux @F1.6
 1920(H) x 1080(V)
 Auto/Manual 1/3 s–1/100000 s
 Auto/natural/street lamp/outdoor/manual/regional custom
 >56dB
 3.6mm (2.8mm optional)
 Auto/Manual
 Instastream; H.265; H.264+; H.264; H.264B; MJPEG (only supported by the sub stream)
 2.8mm: H: 106.0° V: 56.0° D: 126.0° , 3.6mm: H: 87.0° V: 46.0° D: 104.0°
 BLC / HLC / WDR(120dB)
 Main stream:1920 x 1080 (1 fps–25/30 fps)
 Sub stream: 704 x 576 (1 fps–25 fps) 704 x 480 (1 fps–30 fps)
 1080P (1920 x 1080); 1.3MP (1280 x 960); 720P (1280 x 720); D1 (704 x 576/704 x 480); VGA (640 x 480); CIF (352 x 288/352 x 240)
 Disable/Enable (4 areas, rectangle)
 4 areas
 ICR switch
 Yes (4 areas)
 G.711A; G.711Mu; G.726; AAC
 Built-in Mic
 H.264: 32 Kbps–6144 Kbps, H.265: 12 Kbps–6144 Kbps
 HTTP; TCP; ARP; RTSP; RTP; UDP; RTCP; SMTP; FTP; DHCP; DNS; DDNS; PPPoE; IPv4/v6; QoS; UPnP; NTP; RTMP; Multicast; HTTPS; SFTP; 802.1x; ICMP; IGMP; ONVIF (Profile S/Profile G/Profile T); CGI; Milestone; Genetec
 Tripwire, Intrusion
 RJ-45 (10/100Base-T)
 Abnormality detection: Motion detection, video tempering, no SD card, SD card full, SD card error, network disconnected, IP conflict, illegal access, voltage detection
 20 Users
 IR Range of 30 Mtr.

CP- UNC-DB21L3C-MDS

2MP Full HD WDR IR Network Dome Camera - 30Mtr.

Feature

Smart Phone

Micro SD Card

Storage Temperature

Operating Temperature

Humidity

Power Source

Power Consumption

Weatherproof Standard

Casing

Dimension

Weight

Specification

iPhone, iPad, Android Phone

FTP; Micro SD card (max. 256 GB); NAS

-40°C to +60°C (-40°F to +140°F)

-40°C~+60°C, Less than 95%RH

≤95%

DC12V, PoE

< 6.5W

IP67

Metal + Plastic

100.9 mm × Φ109.9 mm (3.97" × Φ4.33")

0.39kg