CS-H6c-R105-1J4WF

Smart Wi-Fi Pan & Tilt Camera




Introduction


EZVIZ products have been designed for your entertainment, communication and security. When you install the EZVIZ App on your smartphone or tablet, EZVIZ devices will be connected to the cloud via their QR code and will immediately be online. With EZVIZ you can talk to your loved ones, watch your child's progress when you are away, keep an eye on your home, interact with your four-legged friends and prevent household accidents.

Main Features

	Motorized Pan and Tilt 360° Visual Coverage with 2K+(4MP) Resolution		Smart Color Night Vision with Light (Up to 5m/16ft)
	Night Vision (Up to 10m/33ft)		Human Shape Detection & Tracking
	Auto-Zoom Tracking	%%	Patrol Mode
\mathcal{Q}	Two-way Calling with Button		Loud Noise Detection
WDR	D-WDR Digital wide dynamic	Þ	Sleep Mode
(((•	2.4/5GHz Dual Band Wi-Fi		MicroSD Slot for Local Storage (Up to 512GB)

Dimension







Specifications

Model	CS-H6c-R105-1J4WF			
Camera				
Resolution	4MP /2K+ Resolution			
Image sensor	F1.6@1/3" Progressive Scan CMOS			
Shutter Speed	Self-adaptive shutter			
Lens	4mm, view angle: 90°(Diagonal), 80° (Horizontal), 43°(Vertical)			
Lens Mount	M12			
Day & Night	IR-cut filter with auto-switching			
DNR	3D DNR			
WDR	Digital WDR			
Compression				
Video Compression	H.264/H.265			
Video Bit Rate	Adaptive bit rate.			
Image				
Max. Resolution	2560 × 1440			
Frame Rate	Max: 30fps; Self-Adaptive during network transmission			
Network	Max. 501ps, Sen / Rapere dailing network dansmission			
Smart Alarm	Motion Detection, Human Shape Detection, Loud Noise Detection, Patrol Mode Detection			
Wi-Fi Pairing	AP paring			
Protocol	EZVIZ cloud proprietary protocol			
Interface Protocol	EZVIZ cloud proprietary protocol			
Interface				
Storage	Micro SD card slot (Max. 512G)			
Power	TYPE-C			
Wired Network	RJ45 X 1 (10M/100M self-adaptive Ethernet port)			
Wi-Fi				
Standard	IEEE802.11a, 802.11b, 802.11g, 802.11n,			
Frequency Range	2.4G: 2400~2483.5MHz			
Channel Bandwidth	5G: 5150MHz-5250MHz			
	Supports 20MHz			
Security Transmission Rate	WPA/WPA2, WPA-PSK/WPA2-PSK			
	11b 11Mbps, 11g 54Mbps, 11nHT20 MCS7, 11a 54Mbps, 11nHT20 MCS7 19 dBm			
Output Power (EIRP) Antenna Gain	1.9 dBi			
General				
Operating Conditions	-10°C to 45°C (14°F to 113 °F), Humidity 95% or less (non-condensing)			
Power Supply	DC 5V/2A			
Power Consumption	8W max			
IR Range	MAX. 10 meters(32. 81ft)			
Dimensions	88mm x 88.2 mm x 119mm (3.46" x 3.47" x 4.69")			
Packaging Dimensions	103mm x 103mm x 168mm (4.06" x 4.06" x 6.61")			
Bare Weight	252 g / 8.9 oz			

